

1505-F-F

CABLE SERIES

Laird 1505-F-F Belden 1505A F-Male to F-Male RG59 Digital Coax Cable

The Laird 1505-F-F series is hand crafted in our shop with Belden 1505A RG59 Precision Video Coax for HD-SDI HDTV and SDI Transmission. These Low Loss Digital Coax Cables are Sweep Tested 5MHz to 1GHz. Available in a variety of lengths and colors.

Features:

- · Belden 1505A cable
- Canare FP-C4F connectors
- Supports 3Gb/s at 212 ft. (SMPTE ST 242) and 6Gb/s at 287 ft. (SMPTE 2081-1)

Specifications:

Number of Coax: 1RG Type: 59/U

• **AWG**: 20

• Stranding: Solid

• Conductor Material: BC - Bare Copper

- Insulation Material: Gas-injected FHDPE Foam High Density Polyethylene
- Outer Shield Material Trade Name: Duofoil
- Outer Shield Material: Dual Shield Bonded Duofoil/TC Tinned Copper
- Outer Jacket Material: PVC Polyvinyl Chloride
- Plenum (Y/N): N
- Plenum Number: BL-1506A
- Nom. Characteristic Impedance: 75 +/- 1.50
- Applications: Precision Video Cable for Analog and Digital, Broadcast Coax, Precision Video Cable for Analog and Digital, HDTV/SDI, Coax Cables





