

Laird DSB-B Canare LV-77S Double-Shielded 75 Ohm BNC to BNC Broadcast Video Cable

The Laird DSB-B series is crafted with highly flexible Canare LV-77S cable and quality 75Ohm Amphenol connectors. Laird BNC cables are useful for both inter-rack harness wiring and longer video cable runs. This super flexible LV-77S type pre-made 75 Ohm BNC-BNC assembly is available in a variety of colors. Our low loss cord offers outstanding video bandwidth performance because all components used are impedance matched for cleaner and sharper video resolution.

## **Features**:

- Super Flexible, Canare LV-77S easy payout & wrap-up
- High Quality True 75 Ohm Amphenol Connectors
- Excellent Connector Pull Strength
- High Density Copper Braid, or Foil + Braid Shields
- Variety of Matte Finish Jacket Colors
- 100% Test and Quality Controlled

## **Specifications:**

- Canare LV-77S 75 Ohm Video Coaxial Cable
- Nom. O.D (mm): 7.7
- AWG: 22
- Inner Cond. O.D (mm): 0.78
- Insulation O.D (mm): 4.8
- Inner Cond. Resist.: 5.0
- Attenuation (dB/100m 10MHz): 3.4



sales@lairddigitalcinema.com WWW.LAIRDDIGITALCINEMA.COM Export Information Country of Origin: USA US ECCN: EAR99 HTS Code: 8544.42 US Dept. of Commerce CCATS: N.a