

XLM-DIN

CABLE SERIES

XLM-DIN DIN 1.0/2.3 to XLR-F Time Code Cable

The Laird XLF-DIN Time Code Cable series features a male Neutrik XLR and a 1.0/2.3 DIN connector for feeding mic level time code from the UltraSync ONE or other DIN time code units to any device that uses a 3-Pin XLR input.

Features:

- Feeds Time Code Signal Through XLR & DIN Connections
- Compatible with the UltraSync ONE
- Neutrik XLR Connector
- DIN 1.0/2.3 Connector
- Belden 4K UHD Precision Video Sub-Miniature Coax Cable

Specifications:

- **Belden 4855R Mini Coax Video Cable**
 - 75 Ohm
 - Nom. Inductance ($\mu\text{H}/\text{ft}$): .107
 - Nom. Capacitance Conductor to Shield (pF/ft): 16.3
 - Max. Recommended Pulling Tension: 40 lbs.
 - Min. Bend Radius/Minor Axis: 1.600 in.
 - Neutrik XLR
 - Capacitance Between Contacts: $\leq 4 \text{ pF}$
 - Contact Resistance: $\leq 3 \text{ m}\Omega$
 - Dielectric Strength: 1,5 kVdc
 - Insulation Resistance: $> 10 \text{ G}\Omega$ (initial)
 - Rated Voltage: $< 50 \text{ V}$
 - Cable O.D.: 3.5 - 8.0 mm
 - Insertion Force: $\leq 20 \text{ N}$
- **1.0/2.3 DIN Connector**
 - Quick Connect Push/Pull system
 - Operation up to 10 GHz

